

IN-CEILING SERIES



OVFRVIFW

Expanding on a proven format, the Explorer Collection benefits from advanced technologies that our engineers have utilized in numerous loudspeaker designs. These loudspeakers are complete updates to our award-winning Director & Composer Collections. Designed for saltwater and sea spray from the beginning, these speakers will hold up in wet rooms, water-front patios, and of course luxury sea-craft.

PRODUCT ID





D105FX

DBA10FX SUBWOOFER

D85FX



COASTAL **IOUDSPFAKERS**

Origin Acoustics' Explorer Collection offers a musical experience that is unparalleled in premium installations. Due to Origin Acoustics' dedication to not only sound reproduction but to functionality and aesthetics, there is no better choice for your yacht or water-front property.

Our loudspeakers disappear into their surroundings while maintaining a maritime weatherproof seal on your bulkheads and ceilings. Coupled with our DSP amplifiers and expert installation, the Explorer Collection delivers a first-class audio adventure.



TRI-LINEAR CONFIGURATION®



We've built an authentic three-way loudspeakerforin-ceiling applications The transducers are stacked linearly for precise imaging and elegantly hinged for an extended pivot. Perfect for creating lifelike sound stages from above.

MULTI-MOTION[™] TWEETER



The secret of Origin Acoustics' superior sound staging is our patented MMP[™] technology. All of our five series and above loudspeakers can pivot up to thirty-degrees. So regardless of placement restrictions, you can direct the sound right to the listener.

Surrounding the interior baffle is a precisely molded rubberized iwwnsert. Its purpose is to absorb errant frequencies that cause phase distortion. This design enhancement ensures that our long-throw woofers and DPSD[™] tweeters are used to their full capabilities.

Using time tested and true technique of compression molding, we designed and produced woofer baskets that are both highly stable and acoustically neutral. The result is a reduction in distortion without coloration from the basket itself.

VARIABLE DEPTH Absorption Layer®



COMPRESSION MOLDED BASKETS





X-WAVE[™] WOOFER SURROUND



When a speaker cone reaches its limit of movement and comes to a hard stop, unwanted waves ripple up and down the cone. Our X-Wave Woofer Surround progressively absorbs that impact, prevented unwanted sonic distortion, and improving overall fidelity.

DPSD[™] TWEETER



MOUNTS IN CEILINGS UP TO 4" THICK.

TOOL-LESS MOUNTING SYSTEM



MAGNETIC GRILLE



This patented tweeter design high-frequency that improves performance, and that prevents distortion and increases loudness. This secondary stabilization allows the driver to be crossed over at a much lower frequency resulting in improved dispersion and decreased distortion.

The Spring-Lock[™] mounting dogs are spring loaded and require only a twist with a thumbnail to have them snap easily and securely into place.

A paintable, perforated grille with a micro bezel covers the entire speaker assembly and leaves a discreet finished appearance. Its magnetic attachment makes removing or replacing the grille fast and easy.



PREMIUM MATERIALS



Pre-stressed woven Kevlar[®] woofers, compression molded baskets, X-Wave[™] Rubber Surround, DPSD[™], Tool-Less Installation, and Low Profile Grilles – The Explorer Collecton has all of the elements of the award-winning Director Collection.

WEATHER PROOF



With an IPX6 rating, the entire Explorer Collection is ready for installation into a wet environment. This rating ensures that your loudspeakers are safe from the corrosion and internal damage commonly posed by exposure to moisture.



SPECIFICATIONS	D105EX	DBA10EX SUBWOOFER	D85EX
Part	SCD100500EX	DBA1000EX	SCD85000EX
Woofer	10" (254mm) IMG	10" (254mm) Glass Fiber	8" IMG
Midrange	4" (100mm) Graphite Pivoting	-	4" IMG MMP
Tweeter	0.75" (19mm) Aluminum	-	1" (25mm) Aluminum MMP
Frequency Response	28 Hz - 20 kHz	35Hz – 200Hz	36Hz-20kHz
Power RMS	50 Watts	50 Watts	50W
Power Peak	150 Watts	150 Watts	150W
Impedance	6 ohm	6 ohm	6 ohm
Diameter	9 ^{3/4} " (247mm)	11 ^{1/4} " (286mm)	9 ^{5/8} " (244mm)
Cutout Diameter	10.375" (264mm)	10 ^{3/8} " (264 mm)	8 ^{3/4} " (222mm)
Grille Diameter	11.625" (296mm)	11 ^{21/32} " (298 mm)	10" (254mm)
Mounting Depth	6.22" (158mm)	6 ^{7/32} " (158 mm)	5 ^{5/8} " (142mm)
Recommended Amp	50 watts - 150 watts		

SPECIFICATIONS

D83EX

D83AEX

D83DT/SUR EX

Part	DSC83000EX	SCD08030AEX	SCDT83000EX
Woofer	8" IMG	8" IMG - Pre-Angled Graphite	8" IMG
Midrange	-	-	-
Tweeter	1" Aluminum MMP	1" Aluminum	Dual 1" Aluminum
Frequency Response	38Hz-20kHz	38Hz-20kHz	38Hz-20kHz
Power RMS	50W	50W	50W
Power Peak	150W	150W	150W
Impedance	6 ohm	6 ohm	6 ohm
Diameter	9 ^{5/8} " (244mm)	9 ^{5/8} " (244mm)	9 ^{5/8} " (244mm)
Cutout Diameter	8 ^{3/4} " (222mm)	8 ^{3/4} " (222mm)	8 ^{3/4} " (222mm)
Grille Diameter	10" (254mm)	10" (254mm)	10" (254mm)
Mounting Depth	4 ^{1/2} " (114mm)	4 ^{11/16} " (119mm)	4 ^{5/16} " (109mm)




SPECIFICATIONS

D65EX

Part	SCD65000EX	
Woofer	6 ^{$1/2$} " IMG Pivoting	
Midrange	-	
Tweeter	1" Aluminum MMP	
Frequency Response	45Hz-20kHz	
Power RMS	40W	
Power Peak	150W	
Impedance	6 ohm	
Diameter	9 ^{5/8} "(244mm)	
Cutout Diameter	8 ^{3/4} "(222mm)	
Grille Diameter	10" (254mm)	
Mounting Depth	5 ^{1/2} " (140mm)	


LINE DRAWINGS



D105EX




LINE DRAWINGS





LINE DRAWINGS





LINE DRAWINGS

